

Check valve

RE 21515/02.06
Replaces: 07.93

1/6

Type Z1SRA

Sizes 16 to 52
 Component series 1X
 Maximum operating pressure 315 bar
 Maximum flow 2000 l/min




Table of contents


Contents	Page
Features	1
Ordering code	2
Standard types	2
Section, symbols	2
Technical data	3
Characteristic curves	4
Unit dimensions	5

Features

- For SAE flange connections as standard or high-pressure version
- Through valve
- Leak-free checking in one direction
- Various cracking pressures, optional

Information on available spare parts:
www.boschrexroth.com/spc




Ordering code



Check valve	
Size 16	= 15
Size 25	= 25
Size 32	= 30
Size 40	= 40
Size 52	= 52
SAE flange connection	
Standard pressure series	= F
High-pressure series	= H

	Further details in clear text
M =	NBR seals (other seals on enquiry) ⚠ Caution! Observe compatibility of seals with hydraulic fluid used!
1X =	Component series 10 to 19 (10 to 19: unchanged installation and connection dimensions)
	Cracking pressure
0 =	Without spring
1 =	See characteristic curves on page 4
2 =	See characteristic curves on page 4
3 =	See characteristic curves on page 4
5 =	See characteristic curves on page 4 (not for sizes 40 and 52)

Section, symbols



Technical data (for applications outside these parameters, please consult us!)

General						
Sizes		Size 16	Size 25	Size 32	Size 40	Size 52
Weight	kg	2.0	2.6	4.0	7.4	12.6
Installation orientation		Optional				
Ambient temperature range	°C	-30 to +80				
Hydraulic						
Maximum operating pressure	bar	315 ¹⁾				
Cracking pressure	bar	See characteristic curve on page 4				
Maximum flow	l/min	See characteristic curve on page 4				
Hydraulic fluid		Mineral oil (HL, HLP) to DIN 51524; fast bio-degradable hydraulic fluids to VDMA 24568 (see also RE 90221); HETG (rape seed oil); other hydraulic fluids on enquiry				
Hydraulic fluid temperature range	°C	-30 to +80				
Viscosity range	mm ² /s	2.8 to 500				
Max. permissible degree of contamination of the hydraulic fluid; cleanliness class to ISO 4406 (c)		Class 20/18/15 ²⁾				






¹⁾ Observe permissible pressures for flange connections (see page 5)!

²⁾ The cleanliness classes specified for components must be adhered to in hydraulic systems. Effective filtration prevents malfunction and, at the same time, prolongs the service life of components.


For the selection of filters, see data sheets RE 50070, RE 50076, RE 50081, RE 50086 and RE 50088.

Characteristic curves (measured with HLP46, $\vartheta_{oil} = 40 \text{ }^\circ\text{C} \pm 5 \text{ }^\circ\text{C}$)

Δp - q_v characteristic curves at cracking pressure



Unit dimensions (nominal dimensions in mm)



Type	Size	B1	B2	H1	H2	L	ØD1	ØD2	ØD3	ØD4	SAE connection
Z1SRA...F...	16	22.2	47.6	60	70	67.5	20	18.5	31.8	11	SAE 3/4"
	25	26.2	52.4	70	80	75	25	21.5	39.7	11	SAE 1"
	32	30.2	58.7	80	95	85	30	26	44.6	11	SAE 1 1/4"
	40	35.8	69.9	95	110	114.5	40	37	54	13	SAE 1 1/2"
	52	42.9	77.8	114	135	129	50	45	63.5	13	SAE 2"
Z1SRA...H...	16	23.8	50.8	60	70	66.5	20	18.5	31.8	11	SAE 3/4"
	25	27.8	57.2	70	80	75	25	21.5	39.7	13	SAE 1"
	32	31.8	66.7	80	95	85	30	26	44.6	15	SAE 1 1/4"
	40	36.6	79.4	95	110	114.5	40	37	54	17	SAE 1 1/2"
	52	44.4	96.8	114	135	129	50	45	63.5	21	SAE 2"

Type	Size	Valve fixing screws (separate order) ¹⁾	Tightening torque M_T in Nm ²⁾	Permissible pressures for flange connections according to	
				ISO 6162/1	ISO 6162/2
Z1SRA...F...	16	M10	70	5000 psi	350 bar
	25	M10	70	4500 psi	315 bar
	32	M10	70	3600 psi	250 bar
	40	M12	130	2900 psi	200 bar
	52	M12	130	2900 psi	200 bar
Z1SRA...H...	16	M10	70	-	6000 psi
	25	M12	130		
	32	M14	180		
	40	M16	295		
	52	M20	550		
					400 bar

¹⁾ 4 hexagon socket head cap screws ISO 4762 - 10.9

²⁾ Data in accordance with ISO 6162, with friction coefficient $\mu_{total} = 0.14$ (please adjust in the case of changed surfaces)

Notes

Bosch Rexroth AG
Hydraulics
Zum Eisengießer 1
97816 Lohr am Main, Germany
Phone +49 (0) 93 52 / 18-0
Fax +49 (0) 93 52 / 18-23 58
documentation@boschrexroth.de
www.boschrexroth.de

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. Without their consent it may not be reproduced or given to third parties.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.

Notes

Bosch Rexroth AG
Hydraulics
Zum Eisengießer 1
97816 Lohr am Main, Germany
Phone +49 (0) 93 52 / 18-0
Fax +49 (0) 93 52 / 18-23 58
documentation@boschrexroth.de
www.boschrexroth.de

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. Without their consent it may not be reproduced or given to third parties.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.

Notes

Bosch Rexroth AG
Hydraulics
Zum Eisengießer 1
97816 Lohr am Main, Germany
Phone +49 (0) 93 52 / 18-0
Fax +49 (0) 93 52 / 18-23 58
documentation@boschrexroth.de
www.boschrexroth.de

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. Without their consent it may not be reproduced or given to third parties.

The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.